

Enclosure selection overview

The table below shows an overview of the terminal options available in each of the enclosures manufactured by Hawke International.

We understand the specification of a suitable enclosure can at first seem complex and daunting. The information below may help in the selection of a suitable enclosure using just the minimum amount of available information, such as the number of terminals needed, operating temperature or the maximum conductor acceptance.

Please see individual datasheets for full enclosure specifications

| Selection Table | | | | | | | | |
|-----------------|-----------------|-----------------------------|-----------------------------|-----------------------|-----------------------|-----------------|-------------------------------|-------------------|
| | Max M20 entries | Max number of 2.5 terminals | Max terminal conductor size | Min operating temp °C | Max operating temp °C | Max voltage (V) | Available with viewing window | Standard Material |
| PL612 | 8 | 12* | 10mm ² | -60 | +75 | 690 | NO | GRP |
| PL712 | 8 | 12* | 10mm ² | -60 | +75 | 690 | NO | GRP |
| PL615 | 8 | 14 | 16mm ² | -60 | +75 | 690 | NO | GRP |
| PL722 | 14 | 35 | 10mm ² | -60 | +75 | 690 | NO | GRP |
| PL620 | 24 | 24 | 70mm ² | -60 | +75 | 690 | NO | GRP |
| PL626 | 24 | 38 | 35mm ² | -60 | +75 | 690 | NO | GRP |
| PL630 | 40 | 76 | 70mm ² | -60 | +75 | 690 | NO | GRP |
| EJB 1 | 16 | 12 | 10mm ² | -60 | +80 | 690 | NO | 316L |
| EJB 2 | 22 | 18 | 16mm ² | -60 | +80 | 690 | NO | 316L |
| S1 | 12 | 30 | 35mm ² | -60 | +80 | 690 | NO | 316L |
| S2 | 28 | 78 | 70mm ² | -60 | +80 | 1100 | YES | 316L |
| S2L | 34 | 117 | 70mm ² | -60 | +80 | 1100 | YES | 316L |
| S3 | 48 | 126 | 70mm ² | -60 | +80 | 1100 | YES | 316L |
| S4 | 54 | 189 | 150mm ² | -60 | +80 | 1100 | YES | 316L |
| S4L | 78 | 252 | 150mm ² | -60 | +80 | 1100 | YES | 316L |
| S5 | 90 | 249 | 150mm ² | -60 | +80 | 1100 | YES | 316L |
| S6 | 150 | 416 | 300mm ² | -60 | +80 | 1100 | YES | 316L |
| S7 | 182 | 640 | 300mm ² | -60 | +80 | 1100 | YES | 316L |
| S8 | 200 | 912 | 300mm ² | -60 | +80 | 1100 | YES | 316L |
| S9 | 228 | 1232 | 300mm ² | -60 | +80 | 1100 | YES | 316L |
| Eze22 | 20 | 76* | 50mm ² | -40 | +80 | 690 | NO | 316L |
| Eze42 | 40 | 114* | 50mm ² | -40 | +80 | 690 | NO | 316L |
| Eze62 | 60 | 190* | 50mm ² | -40 | +80 | 690 | NO | 316L |

* WDU 2.5N

Information contained above is for quick reference only - see individual datasheets for specific information